

## EARTHKEEPER® WRL BIODEGRADABLE WIRE ROPE LUBRICANT

Wire ropes are a machine component. Like any other machine component, they have moving parts that require lubrication. Bending and stretching of the rope results in friction and a good anti-wear lubricant is called for. Earthkeeper® WRL penetrates to the core, ensuring that the rope is lubricated throughout. The oil is treated with additives that enhance anti-wear capabilities and even provide a degree of extreme pressure protection. Wire rope life is extended. Downtime for rope changes is reduced and production is increased.

Earthkeeper® WRL is ideal for marine environments. Negative consequences from accidental spillage are greatly reduced, as it easily passes all tests for biodegradability and is classified as “Readily Biodegradable”.

Earthkeeper® Wire Rope Lubricant has been tested by an independent lab and found to contain 95% renewable (“biobased”) materials.

### BENEFITS:

- **BIODEGRADABLE** – an ethical and safe choice for use in sensitive areas.
- **WEAR PROTECTION** – extreme load carrying extends rope life.
- **RUST RESISTANCE** – outstanding protection.
- **MULTI-GRADE** – reduces viscosity variations with changing temperatures.

### APPLICATIONS:

Use Earthkeeper® WRL for all wire ropes, especially those in ecologically sensitive areas and near waterways.

ASTM #		TYPICAL CHARACTERISTICS
D-445	<b>Kinematic Viscosity</b> cSt @ 40°C cSt @ 100°C	24.4 5.9
D-2270	<b>Viscosity Index</b>	205
D-97	<b>Pour Point, °F (°C)</b>	-35 (-37)
<b>Gardner Method</b>	<b>Density, lb/gal @ 60°F (15.5°C)</b> <b>Specific Gravity, g/cc @ 60°F (15.5°C)</b>	7.64 0.918
D-92	<b>Flash Point, °F (°C)</b> Cleveland Open Cup	320 (160)
D-2783	<b>Four Ball EP</b> Weld Point, kg	250
D-4172	<b>Four Ball Wear</b> Scar Wear, mm	0.40
D-665	<b>Rust Test</b>	Pass

*The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

### PACKAGING

Shuttle Tanks	Drums	Pails
---------------	-------	-------

For warranty information, scan the QR code.  
You can also email us at [sales@whitmores.com](mailto:sales@whitmores.com)  
Or write to the Sales Department at the address below.

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318  
An ISO 9001 and ISO 14001 registered company • [www.whitmores.com](http://www.whitmores.com)

