EXTENDED HANDWHEEL HOISTS

1/2 to 6 ton

CAPACITIES EXTENDED HANDWHEEL 3 feet standard


LIFT 8 feet standard **OPTIONS**

Spark & Corrosion Resistance

The Extended Handwheel version of the Chester Zephyr hoist allows the operator to stand at a distance from the load. Handling materials from a distance, or work whose surface must be protected from scratching by the hand chain, or large flat or bulky loads, are some of the practical applications. Suspension may be from fixed supports or on trolleys.

KEY FEATURES

CHESTER ZEPHYR HOISTS WITH EXTENDED HANDWHEELS CONTAIN ALL OF THE SAME KEY FEATURES AS THE HOOK SUSPENDED MODELS.



DIMENSIONS

Capacity (tons)	Dimensions (in.)										
	Α	В	С	D	Е	F	G	н	ı	J	
REGULA	AR UN	ITS									
1/2	12-1/8	29-7/16	7-1/4	4-1/4	6-9/16	41-7/16	1	4-21/32	6-7/16	1	
1	12-1/4	29-7/16	7-1/4	4-1/4	6-9/16	41-7/16	1	4-21/32	6-7/16	1	
1-1/2	15-7/8	29-1/2	9-3/4	5	6-1/2	42-1/4	1	5-21/32	7-5/8	1-1/8	
2	15-7/8	29-1/2	9-3/4	5	6-1/2	42-1/4	1	5-21/32	7-5/8	1-1/8	
SPARK-	SPARK-RESISTANT UNITS										
1/2											
1											
1-1/2											
2											

Capacities beyond 2 Ton contact factory





SPECIFICATIONS

Capacity	Catalog	Standard	Hand Exte	Net								
(tons)	Number	Lift (ft.)	Standard (ft.)	Maximum (ft.)	Weight (lbs.)							
REGULAR UNITS												
1/2	134 - 1/2	8	3	10	78							
1	134 - 1	8	3	10	84							
1-1/2	134 - 1-1/2	8	3	10	115							
2	134 - 2	8	3	10	125							
SPARK-RESISTANT UNITS												
1/2												
1												
1-1/2												
2												

Capacities beyond 2 Ton contact factory