

ZEPHYR TWIN HOOK HOISTS

CAPACITIES 1/2 to 6 ton	HOOK SPACING 3 feet standard (up to 16 ft.)	LIFT 8 feet standard	OPTIONS Spark & Corrosion Resistance
-----------------------------------	---	--------------------------------	--

Chester Zephyr hoists are available with hooks up to 16 feet between centers and extra length lifts as needed. The Twin Hook Hoist drives two separate load chains simultaneously from a single hand chain. Long and bulky loads can be more easily and evenly lifted with the Twin Hook Hoist. It handles such unwieldy pieces as tubes, frames, towers, drying and storage racks, auto and truck bodies, vats and tanks. Suspension hooks can be hung from trolleys or fixed positions.

KEY FEATURES

CHESTER ZEPHYR TWIN HOOK HOISTS CONTAIN ALL OF THE SAME KEY FEATURES AS THE HOOK SUSPENDED MODELS.

SPECIFICATIONS

Capacity (tons)	Catalog Number	Standard Lift (ft.)	Chain Pull to Lift Full Load One Foot (lbs.)	Chain Overhauled to Lift Load One Foot (ft.)	Net Weight (lbs.)
REGULAR UNITS					
1/2	133 - 1/2	8	35	33	106
1	133 - 1	8	70	33	162
1-1/2	133 - 1 1/2	8	64	58	287
2	133 - 2	8	83	58	412
3	133 - 3	8	66	116	535
4	133 - 4	8	86	116	592
5	133 - 5	8	71	174	715
6	133 - 6	8	86	174	715
SPARK-RESISTANT UNITS					
1/2					
1					
1-1/2					
2					
3					
4					
5					
6					
8					
10					

Center baring required for shafts over 10 ft.
Capacities beyond 6 Ton contact factory



1/2 TO 6 TON

DIMENSIONS

Capacity (tons)	Dimensions (in.)								
	A	B (standard)	C	D	E	F	H	I	J
REGULAR UNITS									
1/2	12-1/8	36	7-1/4	4-1/4	4-1/4	3	1-3/8	5-7/8	1
1	12-1/4	36	7-1/4	4-1/4	4-1/4	3	1-3/8	5-7/8	1
1-1/2	15-7/8	36	9-1/4	5	5	3-1/4	1-3/4	8-1/8	1-1/8
2	15-7/8	36	9-3/4	5	5	3-1/4	1-3/4	8-1/8	1-1/8
3	23-1/2	36	9-3/4	5	5	3-1/4	4-7/8	9-1/8	1-11/32
4	24-1/2	36	9-3/4	5	5	3-1/4	4-7/8	9-5/8	1-11/16
5	25-1/2	36	9-3/4	5	5	3-1/4	6-3/8	11-1/2	1-11/16
6	25-1/2	36	9-3/4	5	5	3-1/4	6-3/8	11-1/2	1-11/16
SPARK-RESISTANT UNITS									
1/2									
1									
1-1/2									
2									
3									
4									
5									
6									
8									
10									