



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER GPO 40 MOTOR OIL

DESCRIPTION

Meets or exceeds the following specifications:

- ⇒ API CF-2, CF
- ⇒ Detroit Diesel 2-stroke cycle engines, Oil Type 1 (1.0 % max. Sulfated ash)

APPLICATIONS

LUBRIPLATE Super GPO 40 Motor Oil is a high-quality diesel engine oil designed for use in a wide variety of applications, including off-highway diesel equipment, farm machinery, marine engines, 2-stroke cycle diesel engines (in the appropriate viscosity grades) and mixed commercial fleets. It may be also used in some heavy duty manual transmissions in trucks and busses.

ADVANTAGES

- ⇒ Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- ⇒ Protects against sludge and varnish formation
- ⇒ Protects against scuffing and wear
- ⇒ Protects against rust and bearing corrosion
- ⇒ Good resistance to foaming and aeration
- ⇒ Low-ash content to minimize the formation of ash deposits and helps keep intake ports clean

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	142
Viscosity cSt @ 100°C	ASTM D-445	15.0
SAE Grade		40
Specific Gravity @ 60°F		0.886
Viscosity Index	ASTM D-2270	106
Pour Point °C(°F)	ASTM D-5950	-27 (-17)
TBN	ASTM D-2896	6.8
High-Temp/High Shear Viscosity, cP @ 150°C		4.2
Zinc, wt %	ASTM D 5185	0.077
Sulfated Ash % wt	ASTM D-874	0.9

PACKAGING AVAILABLE

5 Gallon Pail
55 Gallon Drum

Part No.

L0752-060
L0752-062