



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE SUPER GPO 30 MOTOR OIL

### DESCRIPTION

LUBRIPLATE Super GPO 30 Motor Oil is premium quality engine oil for all-season use in commercial mixed-fleet engine operations. LUBRIPLATE Super GPO 30 Motor Oil is manufactured to meet the performance requirements in all naturally aspirated, turbocharged and supercharged diesel engines as well as all four-cycle gasoline engines.

#### Meets or exceeds the following specifications:

- ⇒ API CF/SL
- ⇒ MIL-PRF-2104G

### APPLICATIONS

LUBRIPLATE Super GPO 30 Motor Oil is recommended for all major automotive diesel and mixed fleet (diesel/four cycle gasoline engines) operations in all service and under all operating conditions where the equipment owner specifies the use of single grade engine oils.

LUBRIPLATE Super GPO 30 Motor Oil may also be used for Hydraulic systems and some hydrostatic transmissions in mobile off-road equipment.

### ADVANTAGES

- ⇒ Resisted breakdown under high temperatures
- ⇒ Maintained oil pressure under heavy load conditions
- ⇒ Minimized rust and corrosion
- ⇒ Good low temperature pour point

### Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	99.0
Viscosity cSt @ 100°C	ASTM D-445	11.8
SAE Grade		30
Viscosity Index	ASTM D-2270	108
Specific Gravity at 60°F		0.884
Sulfated Ash % wt	ASTM D-874	1.3
Flash Point °C (°F)	ASTM D-92	230 (446)
Pour Point °C (°F)	ASTM D-5950	-33 (-27)
TBN	ASTM D-2896	10.5

### PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles  
5 Gallon Pail  
55 Gallon Drum

### Part No.

L0749-054  
L0749-060  
L0749-062