



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SUPER GPO 15W-40 CK-4

DESCRIPTION

LUBRIPLATE Super GPO 15W-40 CK-4 is a heavy duty, extra high performance synthetic blend multi-grade engine oil that provides excellent protection in diesel fuel and gasoline engines over a wide range of operating conditions and performance demands. Compounded with detergents, dispersants, wear control elements, antioxidants, corrosion inhibitors and foam suppressant additive. Extremely resistant to development of high temperature deposits and low temperature sludge clogging, inhibit ring deposit formation, reduces engine wear associated with increased soot levels and improved oil consumption control. Suitable for use in almost all foreign and domestic engines, gasoline or diesel, naturally aspirated or turbocharged. Always consult your owner's manual for proper application.

ADVANTAGES

- ⇒ Superior soot handling and wear control
- ⇒ Excellent EGR emission control performance
- ⇒ Outstanding oxidation stability
- ⇒ Excellent low temperature properties helps speed cold starts
- ⇒ Synthetic-blend
- ⇒ Universal product for consolidation of products

APPLICATIONS

LUBRIPLATE Super GPO 15W-40 CK-4 is formulated to offer superior performance in today's high performance, fuel efficient, low-emission diesel and gasoline engines. It is recommended for use in naturally aspirated, turbo-charged, or super charged diesel, gasoline and propane engines, including those featuring EGR or other technologies for emissions control.

RECOMMENDATIONS

- ⇒ API CK-4, CJ-4, CI-4 plus, or CI-4, PLUS, SN
- ⇒ ACEA E9
- ⇒ Caterpillar ECF-3, ECF-2, ECF-1-a
- ⇒ Chrysler MS-10902
- ⇒ Cummins CES 20086, 20087, 20081
- ⇒ Mack EOS-4.5, EO-0 Premium Plus, EO-N
- ⇒ Mercedes Benz 228.31
- ⇒ Detroit Diesel DFS 93K222, DFS 93K233, DFS 93K218
- ⇒ Ford WSS-M2C171-F1
- ⇒ MTU MTL 5044 Type 2.1
- ⇒ Renault RLD-4, RLD-3
- ⇒ Volvo VDS-4.5

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity cSt @ 40°C	ASTM D-445	113.9
Viscosity cSt @ 100°C	ASTM D-445	15.6
Viscosity Index	ASTM D-2270	145
Cold Cranking Simulator, cP at °C	ASTM D-5293	5500 @ -20
Pour Point, °C (°F)	ASTM D-5950	-33 (-27)
Flash Point, °C (°F)	ASTM D-92	226 (438)
Total Base Number	ASTM D-974	10.0
Sulfated Ash, wt %	ASTM D-874	1.0

PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles
Carton, 2/2½ Gallon Jugs
5 Gallon Pail
55 Gallon Drum

Part No.

L0755-054
L0755-055
L0755-060
L0755-062