



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE MP-4 Multipurpose Lubricant Penetrating Oil

DESCRIPTION

ONE PRODUCT TO SATISFY FOUR IMPORTANT CONSIDERATIONS:

- ⇒ Protects against Wear
- ⇒ Releases Stuck Parts
- ⇒ Prevents Rust
- ⇒ Displaces Moisture

APPLICATIONS & ADVANTAGES

Moisture Displacement

- ⇒ An excellent "wet start" product, featuring outstanding moisture displacement properties

Rust Preventive Coating

- ⇒ Possesses exceptional rust-proofing properties. Thirty-day test in humidity cabinet prove its rust-proofing properties. Light in viscosity, promotes rapid and complete draining.
- ⇒ Highly recommended for rust-proofing machine tool parts, steel cast parts, etc.

Penetrating Fluid

- ⇒ Exceptional penetration properties.
- ⇒ Recommended for nuts, bolts, valves, heat risers, cables, linkage, etc.

Lubricant

- ⇒ In addition to all the other properties, recommended for permanent and positive lubrication over a long period of time.
- ⇒ Aerosol package utilizes LUBRIPLATE'S SECURE STRAW DUAL SPRAY NOZZLE

Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS* |
|------------------------|--------------|------------------|
| Viscosity: SUS @ 100°F | ASTM D-2161 | 45 |
| cSt @ 40°C | ASTM D-445 | 6 |
| SUS @ 210°F | ASTM D-2161 | 31 |
| cSt @ 100°C | ASTM D-445 | 1.5 |
| Flash Point | ASTM D-92 | 280°F/138°C |
| Fire Point | ASTM D-92 | 305°F/152°C |
| Dielectric Strength | ASTM D-877 A | 42 kV (average) |
| Color | ASTM D-1500 | 5 |
| Appearance | Visual | Clear to Hazy |

PACKAGING AVAILABLE

- Carton 12/12 oz. Aerosol Cans
- Case 12/1 pint Pump Spray
- 1 Gallon Jug/Case of 4
- 55 gal. Drum

Part No.

- L0722-063
- L0722-067
- L0722-057
- L0722-062