

HyFilm® EPG Engine Oil



HyFilm® EPG uses state-of-the-art technology to protect modern gasoline engines while maximizing fuel economy and extending service intervals. **HyFilm EPG** exceeds the latest API and ILSAC and General Motors dexos®1 specifications. Designed to meet the rigorous demands of modern high output turbocharged and supercharged gasoline engines, **HyFilm EPG** is also backward compatible to provide lubrication across the entire range of gasoline engines.

HyFilm EPG Official Approvals:

API SQ Resource Conserving	ILSAC GF-7A	
-----------------------------------	--------------------	--

HyFilm EPG Meets or Exceeds:*

Ford WSS-M2C970-A1 (5W-20)	Ford WSS-M2C971-A1 (5W-30)	Chrysler MS-6395T
-----------------------------------	-----------------------------------	--------------------------

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES	
SAE Grade	SAE J300	5W-20	5W-30
Kinematic Viscosity, cSt @ 40°C	ASTM D445	49.23	63.04
Kinematic Viscosity, cSt @ 100°C	ASTM D445	8.94	10.74
Viscosity Index No.	ASTM D2270	164	161
CCS Viscosity, cP @ -30°C	ASTM D5293	4034	5718
High Temp High Shear Viscosity, cP @ 150°C @ 10⁶ s⁻¹	ASTM D4683	2.83	3.3
Density, kg/l @ 15.5°C	ASTM D1298	.8500	0.8516
Pour Point, °F (°C)	ASTM D97	-38.2 (-39)	-34.6 (-37)
Flash Point, °F (°C)	ASTM D92	392 (200)	394 (201)
Noack Volatility, % wt. loss	ASTM D5800	10.2	8.7
TBN (Total Base Number)	ASTM D2896	7.9	8.0
TBN (Total Base Number)	ASTM D4739	6.0	6.0
Sulfated Ash, % wt.	ASTM D874	0.80	0.76
Color		Amber	Amber

*Guaranteed to meet or exceed specifications, not officially licensed.