

No. 30 INDUSTRIAL WAY OIL

Industrial Lubricant

No. 30 INDUSTRIAL WAY OIL is specially designed for the stick slip motion found in machine ways. **No. 30 Industrial Way Oil** is formulated with the latest additive technology for balanced wear protection, friction control, and rust and corrosion protection.

TYPICAL APPLICATIONS INCLUDE:

Milling machines	Horizontal boring machines	Gear cutters	Metal forming
Planers	Jig borers	Hobbing machines	Saw guides
Worm gears	Shapers	Lathes	Grinders

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES	
ISO Grade	ASTM D2422	68	220
AGMA No.		2EP	5EP
SAE Viscosity Grade	SAE J300	20	50
Kinematic Viscosity, cSt @ 40°C	ASTM D445	68	220
Kinematic Viscosity, cSt @ 100°C	ASTM D445	9.23	20.52
Viscosity Index No.	ASTM D2270	112	109
Density, lb/gal @ 15.5°C	ASTM D1298	7.22	7.29
Density, g/ml @ 15.5°C	ASTM D1298	0.8653	0.8733
Pour Point, °F (°C)	ASTM D97	5 (-15)	10 (-12)
Flash Point, °F (°C)	ASTM D92	401 (205)	482 (250)
Copper Strip Corrosion, 100°C, 3 hr	ASTM D130	1a	1a
Rust Test, Distilled Water	ASTM D665A	Pass	Pass
Rust Test, Synthetic Sea Water	ASTM D665B	Pass	Pass
Demulsibility	ASTM D1401	Pass	Pass
Foaming Test, Sequence I, II, III	ASTM D892	Pass	Pass
Color		Light Amber	Amber

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 75 years of innovation resulting in superior lubrication solutions and high touch customer service.