

Majestic™ 261 Fire Resistant Hydraulic Fluid ISO 46

Majestic 261 Fire Resistant Hydraulic Fluid is a high performance fire resistant hydraulic fluid for use near glass and metal furnaces or other applications where hydraulics leaks may pose a fire hazard.

This product contains water-glycol base fluid, do not mix with other hydraulic fluid types. Do not use with asbestos, leather, or cork-impregnated seals. Do not use in hydraulic systems containing solder, tin, zinc, magnesium or cadmium.

TYPICAL APPLICATIONS INCLUDE:

Hydraulic Systems

Metal Manufacturing

Glass Manufacturing

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
ISO Grade	ASTM D2422	46
SAE Grade	SAE J-300	20W
Viscosity Index No.	ASTM D2270	180
Density, kg/L @ 60 °F	ASTM D1298	1.08
Density, Lb/gal. @ 60 °F	ASTM D1298	9.01
Pour Point, °F (°C)	ASTM D97	-50 (-46)
Flash Point, °F (°C)	ASTM D92	N/A
Autoignition Temperature, °F (°C)	ASTM D286	765 (407)
Rust Test, Distilled Water	ASTM D665	Pass
pH @ 77 °F, (25 °C)	ASTM D892	9.5
Color		Red

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 80 years of innovation resulting in superior lubrication solutions and high touch customer service.