

Majestic™ Engine Oil SAE 15W-40

Majestic Engine Oil SAE 15W-40 meets the rigorous demands of today's high output, low emissions diesel engines and is also backward compatible to provide lubrication across the entire range of 4-stroke diesel engines.

Majestic Engine Oil SAE 15W-40 Official Approvals:

API CK-4, CJ-4, CI-4		
----------------------	--	--

Majestic Engine Oil SAE 15W-40 Meets or Exceeds:*

DDC Power Guard 93K222	Volvo VDS-4.5	Cummins CES 20086
Ford WSS-M2C171-F1	Mack EOS-4.5	Renault VI RLD-4
ACEA E9	Caterpillar ECF-3	Mercedes Benz 228.31
MAN 3575†	JASO DH-2	MTU Type 2.1
Deutz DQC III-10 LA		

* Guaranteed to meet or exceed specifications, not officially licensed.

† Meets or exceeds engine test requirements only

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
SAE Grade	SAE J300	15W-40
Kinematic Viscosity, cSt @ 40°C	ASTM D445	112.4
Kinematic Viscosity, cSt @ 100°C	ASTM D445	14.9
Viscosity Index No.	ASTM D2270	137
CCS Viscosity, cP @ -20°C	ASTM D5293	5,700
High Temp High Shear Viscosity, cP @ 150°C @ 10 ⁶ s ⁻¹	ASTM D4683	4.2
Density, kg/l @ 15.5°C	ASTM D1298	0.874
Pour Point, °F (°C)	ASTM D97	-17 (-27)
Flash Point, °F (°C)	ASTM D92	446 (230)
Noack Volatility, % wt. loss	ASTM D5800	11
TBN (Total Base Number)	ASTM D2896	10
TBN (Total Base Number)	ASTM D4739	7
Sulfated Ash, % wt.	ASTM D874	1.0
Sulfur, % wt.	ASTM D4951	0.35
Phosphorus, %wt,	ASTM D4951	0.10
Color		Amber