

HY-TORQUE® LV-ATF

Hydrosynthetic® Automatic Transmission Fluid

Hy-Torque® LV-ATF provides maximum performance and system life for modern automatic transmissions in passenger vehicles.

TYPICAL APPLICATIONS INCLUDE:

Automatic Transmissions
Forklifts

Transfer Cases
Hydrostatic Drives

Power Steering
Hydraulic Systems

Note: Not recommended for use in Continuously Variable Transmissions or Hybrid vehicles with electronic continuously variable transmissions (eCVTs).

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
Kinematic Viscosity , cSt @ 40°C	ASTM D445	31.0
Kinematic Viscosity , cSt @ 100°C	ASTM D445	6.15
Viscosity Index No.	ASTM D2270	152
Brookfield Viscosity , cP @ -40°C	ASTM D2983	<12,000
Density , kg/l @ 15.5°C	ASTM D1298	0.8458
Density , lb/gal @ 60°F	ASTM D1298	7.05
Pour Point , °F (°C)	ASTM D97	-49 (-45)
Flash Point , °F (°C)	ASTM D92	360 (182)
Color		Red

Hy-Torque LV-ATF is recommended for use in applications that require the following specification:

Passenger Car	Dexron® VI	Mercon® LV
	Aisin Warner AW-1	Honda DW-1
	Hyundai/Kia SP-IV, SPH-IV, SP-IV RR	Hyundai NWS-9638
	JASO 1-A-LV	JWS 3324
	Mitsubishi ATF-J2, ATF-PA	Mitsubishi SP-IV
	Nissan MaticS, MaticW	Toyota WS (JWS 3324)
	Audi G 055 005, G 055 162	BMW 83 22 0 142 516, 83 22 2 152 426
	Mercedes-Benz 236.41	Saab 93 165 147
	VW G 052 540, G 055 005, G 055 162	ZF 6 Speed (S671 090 255)
	Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675)	

MERCON® is a registered trademark of Ford Motor Company.

DEXRON® is a registered trademark of General Motors Corp.

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 80 years of innovation resulting in superior lubrication solutions and high touch customer service.