

No. 528 HIGH SPEED CHAIN, WIRE ROPE & CABLE LUBRICANT with MOLY

TYPICAL APPLICATIONS INCLUDE:

Conveyor Chains	Wire Ropes	Tracks and Guide Ways	Chains and Cables
Pins and Bushings	Cams and Slides	Open Bearings	Hinges
Valves	Hemp Core Cable	Leaf Chains	Table Top Chains
Turn-Buckles	Screw Jacks	Solid Core Cable	Leaf Springs

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
Color		Dark Gray
ISO Grade	ASTM D2422	100 to 150
AGMA No.		3 to 4
Viscosity Index	ASTM D2270	105
Kinematic Viscosity, cSt @ 40°C	ASTM D445	112
Kinematic Viscosity, cSt @ 100°C	ASTM D445	12.7
Density, lb/gal, @ 60°F	ASTM D1298	7.45
Density, kg/l @ 15.5°C	ASTM D1298	0.893
Pour Point, °F (°C)	ASTM D97	0 (-18)
Flash Point, °F (°C)	ASTM D92	450 (232)
Four Ball Wear	ASTM D4172	0.40
Rust Test, Distilled Water	ASTM D665A	Pass
Rust Test, Syn. Sea Water	ASTM D665B	Pass

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high-performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 80 years of innovation resulting in superior lubrication solutions and high touch customer service.