

ULTRA-KLEEN™ 604 FOOD GRADE CHAIN & CABLE LUBRICANT

 Lubricants for a Healthier Planet™

Ultra-Kleen™ 604 Food Grade Chain & Cable Lubricant is designed to improve food safety from Field to Fork. It provides high performance chain and cable lubrication for a variety of agricultural machinery used to plant, tend and harvest fruits and vegetables as well as the food processing equipment and packaging machines for the finished consumer product.

All ingredients in **Ultra-Kleen 604 Food Grade Chain & Cable Lubricant** are listed substances generally recognized as safe (GRAS) or substances used in accordance with the provisions of a prior sanction or approval permitted under the rules of the U.S. Food and Drug Administration 21 CFR 178.3570 for lubricants with incidental food contact.

NSF Nonfood Compounds H1 Registered: See Product Attribute Table

ISO 21469 Certification: See Product Attribute Table

Kosher and Pareve Certified



TYPICAL APPLICATIONS INCLUDE:

PTO Chains & Sprockets	Cables and wire ropes	Track and Guide Ways
Pins and Bushings	Cams and Slides	Drive Chains

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
NSF NFC Registration Number		154018
ISO 21469 Certified		Y
Thickener Type		Aluminum Complex
NLGI Grade	ASTM D217	00-000
Worked Penetration, 1/10th mm	ASTM D217	400-475
Base Oil Kinematic Viscosity, cSt @ 40°C	ASTM D445	105
Base Oil Kinematic Viscosity, cSt @ 100°C	ASTM D445	12.1
Viscosity Index		105
Density, g/ml @ 15.5°C	ASTM D1298	0.89
Density, lb/gal @ 60°F	ASTM D1298	7.44
Pour Point °F (°C)	ASTM D97	0 (-18)
Flash Point °F (°C)	ASTM D1743	420 (215)
4-Ball Wear, scar diameter, mm	ASTM D2266	0.57
Rust Test, Distilled Water	ASTM D665A	Pass
Rust Test, Syn. Sea Water	ASTM D665B	Pass
Color		Translucent White

Ultra-Kleen 604 Food Grade Chain & Cable Lubricant does NOT contain any ingredient with the following allergenic, sensitizing components or allergenic proteins or substances listed in the table below:

Animal Products including Enzymes, Fats or Proteins	Genetically Modified Organisms (GMO)
Eggs	Fish
Peanuts	Soybeans and Products Thereof
Sulfites	Dairy/derivatives
Wheat	Tree Nuts
Gluten (wheat, rye, barley, oats, spelt, kamut)	Shellfish/Crustaceans/Mollusks
Sesame and Products Thereof	Lupine
Mustard and Products Thereof	Celery
Carmines/Cochineal	BHA, butylated hydroxyanisole
MSG, monosodium glutamate	BHT, butylated hydroxytoluene
TBHQ, tertiary butylhydroquinone	Hydrolyzed Vegetable Protein (HVP)
Autolyzed Yeast	Artificial Flavors
FD&C Color	Saccharin

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 80 years of innovation resulting in superior lubrication solutions and high touch customer service.