

Majestic™ 800 Food Grade System Flush

 Lubricants for a Healthier Planet™

Majestic™ 800 Food Grade System Flush is formulated to remove varnish deposits and protect equipment during the flushing procedure in food processing and related industries where H1 lubricants are required. For mild varnish deposits, add as a portion of the existing lubricant, or, for severe deposits or changeover to H1 lubricants, completely drain and fill system with **Majestic Food Grade System Flush**.

All ingredients in **Majestic™ 800 Food Grade System Flush** are listed substances generally recognized as safe (GRAS) or substances used in accordance with the provisions of a prior sanction or approval permitted under the rules of the U.S. Food and Drug Administration 21 CFR 178.3570 for lubricants with incidental food contact.



NSF Nonfood Compounds H1 Registered: See Product Attribute Table

ISO 21469 Certification: See Product Attribute Table

Kosher and Pareve Certified

TYPICAL APPLICATIONS INCLUDE:

Hydraulic Systems	Gearboxes	Bearings	Centralized Lubrication Systems
Compressors	Chain Drives	Rotary Lobe Blowers	

Application Notes: **Majestic 800 Food Grade System Flush** is fully compatible with petroleum hydrocarbon based lubricants, which include white oil, paraffinic or naphthenic mineral oils, and PAO. **Majestic 800 Food Grade System Flush** is proven safe for use with common seals and elastomers that are known to be compatible with petroleum-based products, which include nitrile rubber and fluoroelastomers. For any specific questions regarding compatibility and to discuss the specific application and recommended flushing procedures, please consult with your local sales representative or the Technical Response Team at (972) 389-8581.

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
ISO Grade	ASTM D2422	046
NSF NFC Registration Number		155690
ISO 21469 Certified		✓
Kinematic Viscosity, cSt @ 40°C	ASTM D445	46
Kinematic Viscosity, cSt @ 100°C	ASTM D445	7.8
Density, g/mL @ 15.6°C	ASTM D1298	0.884
Density, lb/gal @ 60°F	ASTM D1298	7.38
Pour Point, °F (°C)	ASTM D97	-11 (-24)
Flash Point, °F (°C)	ASTM D92	513 (267)
Fire Point, °F (°C)	ASTM D92	526 (274)
4-Ball Wear, scar diameter, mm	ASTM D2266	0.36
Fluid Cleanliness	ISO 4406	14/13/11

Note: Fluid may discolor upon exposure to light, which is not an indication of reduced performance or instability.

Majestic 800 Food Grade System Flush does NOT contain any ingredient with the following allergenic, sensitizing components or allergenic proteins or substances listed in the table below:

Animal Products including Enzymes, Fats or Proteins	Fish
Eggs	Soybeans and Products Thereof
Peanuts	Dairy/derivatives
Sulfites	Tree Nuts
Wheat	Shellfish/Crustaceans/Mollusks
Gluten (wheat, rye, barley, oats, spelt, kamut)	Lupine
Sesame and Products Thereof	Celery
Mustard and Products Thereof	BHA, butylated hydroxyanisole
Carmine/Cochineal	BHT, butylated hydroxytoluene
MSG, monosodium glutamate	Hydrolyzed Vegetable Protein (HVP)
TBHQ, tertiary butylhydroquinone	Artificial Flavors
Autolyzed Yeast	Saccharin
FD&C Color	

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 80 years of innovation resulting in superior lubrication solutions and high touch customer service.