

Majestic 1040 Industrial Solvent

Majestic 1040 Industrial Solvent is an industrial strength, concentrated solvent and parts cleaner. This solvent has excellent wetting ability which allows it to penetrate and loosen even the heaviest deposits of grease and grime so they can easily be rinsed away.

Majestic 1040 Industrial Solvent is a mixture of C9-C13 naphthenes, iso- and n-paraffins (hydro-treated, heavy naphtha). Neither the concentration of aromatics nor of hexane is greater than 0.1% by volume.

Majestic 1040 Industrial Solvent quickly and easily liquefies grease, tar, asphalt, oils, dirt, adhesive resin and other deposits. It has low odor and is ideal for degreasing and cleaning most industrial machinery, and automotive parts.

Majestic 1040 Industrial Solvent is Safer to Use and non-chlorinated formula may be used on most plastics, metal, glass, aluminum, porcelain, tile, wood and concrete.

PRODUCT ATTRIBUTE	TEST METHOD	TYPICAL PROPERTIES
Density, LB/gal @ 60°F	ASTM D4052	6.33- 6.59
Density, gm/cc @ 15.5°C	ASTM D4052	0.74 – 0.77
Distillation, DP, °C (°F)	ASTM D86	≤395 (743)
Distillation, IBP, °C (°F)	ASTM D86	≥163 (325.4)
Aromatics	ASTM E169	≤0.1%
Flash Point, °C	ASTM D56	46 – 62
Flash Point, °F	ASTM D56	114.8 – 143.6
Color	-	Colorless

Note: Prior to using on painted surfaces or plastics, test surface compatibility on a small inconspicuous test area before general application.

DANGER: Vapors from this product may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from point of product use. Adequate ventilation must be provided during use. Waste oil mixtures with this product pose a flammability hazard. Contains petroleum distillates. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call a physician immediately. Vapor harmful. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. Extremely flammable. Do not use near fire, flame or while smoking. **KEEP OUT OF REACH OF CHILDREN.**

WARRANTY:

When properly stored and used in accordance with instructions, any material not satisfactory will be replaced with any product in our line on a dollar for dollar basis provided the account is paid in full when due and Hydrotex is notified in writing within 12 months of the date of the order by the customer.

Hydrotex® is a manufacturer and distributor of high performance lubricant and fuel improver solutions. As an employee owned company, we help our customers develop sustainable solutions designed to improve system reliability, save energy, limit pollution, extend fixed asset life, reduce maintenance costs and improve fuel efficiency. Our products and services leverage over 80 years of innovation resulting in superior lubrication solutions and high touch customer service.